



## ZX70 FULLY RUGGED TABLET



- Qualcomm® Snapdragon™ 660, Octa-core Processor
- Verified as Android Enterprise Recommended<sup>1</sup>
- 7" LumiBond® Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810H and IP67 Certified
- Optional Barcode Reader and RFID Reader
- High Sensitivity GPS



Office Dock



Vehicle Dock



# Specifications

## Operating System

Android™ 9.0

## Mobile Computing Platform

Qualcomm® Snapdragon™ 660, Octa-core 1.95 GHz, burst up to 2.2 GHz

## VGA Controller

Qualcomm® Adreno™ 512 GPU

## Display

7" IPS TFT LCD HD (1280 x 720)  
Protection film  
LumiBond® display with Getac sunlight readable technology  
Capacitive multi-touch screen

## Storage & Memory

4GB LPDDR4  
64GB eMMC

## Keyboard

Power button  
3 tablet programmable buttons

## Pointing Device

Touchscreen  
- Capacitive multi-touch screen

## Expansion Slot

MicroSD x1

## I/O Interface

8M pixels webcam x 1  
12M pixels auto focus rear camera x 1  
DC in Jack x 1  
USB 2.0 (Host) x 1  
MicroUSB 2.0 (Client) x 1  
Docking Connector (Pogo / JAE) x 1  
MicroSD x 1  
Optional: RF antenna pass-through for GPS and WWAN

## Communication Interface

Wi-Fi 802.11ac  
Bluetooth (v5.0)<sup>ii</sup>  
Dedicated GPS  
Optional: 4G LTE mobile broadband

## Security Feature

Optional: Contactless HF RFID / NFC combo reader<sup>iii</sup>  
Optional: Barcode reader

## Power

AC adapter (25W, 100-240VAC, 50 / 60Hz)  
Li-Ion battery (3.8V, typical 8480mAh; min. 8220mAh)

## Dimension (W x D x H) & Weight

218 x 142 x 27 mm (8.58" x 5.6" x 1.08")  
762 g (1.68 lbs)<sup>iv</sup>

## Rugged Feature

MIL-STD-810H certified  
IP67 certified  
Vibration & 6 feet drop resistant  
Optional: ANSI / UL 121201, CSA C22.2 NO. 213

## Environmental Specification

Temperature:<sup>v</sup>  
- Operating: -21°C to 60°C / -6°F to 140°F  
- Storage: -40°C to 71°C / -40°F to 160°F  
Humidity:  
- 95% RH, non-condensing

## Pre-installed Software

Getac File Browser  
Getac Camera  
Getac Input Method  
DeployeXpress Client  
Getac Settings and Google Applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play Music, Play Movies, Duo and Photos)

## Accessories

AC Adapter (25W; 12V/2A, 100-240VAC; 50 / 60 Hz)  
Capacitive Stylus  
Pen holder  
Wrist Strap

## Optional:

Carry Bag  
AC Adapter (25W; 12V/2A, 100-240VAC; 50 / 60 Hz)  
Office Dock AC Adapter (60W, 110-240VAC)  
Vehicle Adapter (40W 11-16V, 20-32VDC)  
Capacitive Stylus  
Protection Film  
Shoulder Strap (2-point)  
Wrist Strap  
Rotating Hand Strap with Kickstand and Stylus Holder  
USB to RS232 Converter Cable  
Docking Connector to HDMI Converter Cable  
Vehicle Dock  
Office Dock

## Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

## Standard

3 years Bumper-to-Bumper

- i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- ii 13.56MHz Contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- iii HF RFID / NFC combo reader applies to US & EU.
- iv Weight and dimensions vary from configurations and optional accessories.
- v Tested by a national independent third party test lab following MIL-STD-810H.

# ZX70

## Fully Rugged Tablet



## Docking Solutions

	Getac-made Vehicle Dock (JAE)	Havis Vehicle Dock (JAE)	Gamber-Johnson Charging Cradle (Pogo)	Havis Vehicle Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1	1	--	1	--	--
Speaker	1	--	--	--	--	--
Audio Output	1	1	--	1	1	1
DC in Jack	1	1	1	1	1	1
USB	USB Host x 2	USB2.0 x 2	--	USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1	1	--	1	1	1
HDMI	1	1	--	--	1	--
RF antenna connector	(WWAN, GPS)	(WWAN, GPS)	--	(WWAN, GPS)	--	--

# Getac

## GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,  
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.  
Tel : +886 2 2785 7888  
globalmarketing@getac.com | www.getac.com



Copyright © 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.  
Information provided herewith is for reference only,  
available specification shall be subjected to quotation by request. V01M10Y20WWW